



GREWIN INDUSTRIAL GROUP CO.,LTD.

TEL/WhatsApp: +86 18622096679

Mail: admin@coilwindingmachinechina.com

Web: www.coilwindingmachinechina.com



WhatsApp



WeChat

GWS580 Computer automatic core winding machine (5 axis)

(1) Technical specifications

Equipment name: Computer automatic core winding machine (5 axes)

Equipment model: GWS580

Equipment size: 195CM*120CM*185CM

Equipment weight: 2300KG

Power supply specification: 380VAC 50/60HZ

Power consumption: 3000W

Air pressure: 7KG

Interface introduction: Simplified Chinese

Production function: Toroidal

Number of servo axes: 5 axes

Distance from knife to shaft: 280mm

Minimum inner diameter: 30mm

Maximum inner diameter: 180mm

Maximum outer diameter: 250mm

Steel sheet width: 10-80mm

Steel sheet thickness: 0.15-0.5mm

GREWIN INDUSTRIAL GROUP CO.,LTD.

Add: The fourth floor A-A3 zone aviation business area, Dongli Distr, Tianjin, China.



GREWIN INDUSTRIAL GROUP CO.,LTD.

TEL/WhatsApp: +86 18622096679

Mail: admin@coilwindingmachinechina.com

Web:www.coilwindingmachinechina.com



WhatsApp



WeChat

Precision on both sides of the core: <0.2mm

Laser welding: equipped with the machine body

Maximum output power: 1000W

Light output mode: continuous optical fiber welding

Cooling mode: pure water circulation cooling

Unloading machine: equipped with the machine body

Unloading machine inner diameter: 450-530mm

Unloading machine outer diameter: 1000-1300mm

Expansion and contraction mode: hydraulic tensioning

Unloading speed: 200M

(2) Machine introduction

1) Computer-automated production provides high precision and high efficiency, reducing post-processing costs and labor requirements.

2) Fully closed-loop monitoring of the entire feeding, clamping, buckling, lifting, winding, cutting, welding and each process, which are completed simultaneously during the rolling production process.

3) The human-machine interface has clear and easy-to-understand pictures, and the control system has multiple automatic calculation functions. Input basic parameters to start production.

4) The entire machine uses world-famous imported accessories, including

GREWIN INDUSTRIAL GROUP CO.,LTD.

Add: The fourth floor A-A3 zone aviation business area,Dongli Distr,Tianjin,China.



GREWIN INDUSTRIAL GROUP CO.,LTD.

TEL/WhatsApp: +86 18622096679

Mail: admin@coilwindingmachinechina.com

Web:www.coilwindingmachinechina.com



WhatsApp



WeChat

Taiwan Delta servo system and computer, SMC pneumatic components, Taiwan servo reducer, and other European and Japanese electrical accessories, etc.

(3) Introduction to the machine

1) Use five-axis Delta servo motor

A) First axis: die-cutting moving servo motor, which moves backward after the sheet is cut, allowing the clamping robot to feed the material to the spindle.

B) Second axis: material-cutting servo motor, connected to imported servo reducer and punching structure, can generate pressure below 8 tons, and can cut silicon steel sheets of 0.5mm or less.

C) Third axis: spindle servo motor, connected to imported servo reducer, drives the spindle to roll the material, with strong torque and high rotation positioning accuracy.

D) Fourth axis: material-returning servo motor, responsible for flattening and pushing out the iron core during the production process.

E) Fifth axis: clamping and feeding servo motor, which clamps the sheet to the roll die hook pin and buckles it firmly.

2) This machine uses Panasonic's high-performance PLC control system, with accurate output pulses, faster and more stable operation speed, and

GREWIN INDUSTRIAL GROUP CO.,LTD.

Add: The fourth floor A-A3 zone aviation business area,Dongli Distr,Tianjin,China.



GREWIN INDUSTRIAL GROUP CO.,LTD.

TEL/WhatsApp: +86 18622096679

Mail: admin@coilwindingmachinechina.com

Web: www.coilwindingmachinechina.com



WhatsApp



WeChat

multiple operations written into the program, which can greatly reduce the operator's debugging time. All actions of the entire machine are equipped with self-protection programs to prevent unnecessary damage. Fully closed-loop control monitors the entire production process, including clamping, buckling, lifting, winding, cutting, welding, demoulding, etc. The human-machine interface uses a 10-inch color screen from Taiwan Vinylon, and the interface is clear, simple and easy to understand.

3) Precision ball screws are all from well-known Taiwanese brands, providing excellent precision and durability.

4) Pneumatic components use SMC series, including various cylinders, solenoid valves, magnetic sensors, precision pressure regulators, filters, air pipes and all joints, etc.

5) Electric lifting platform, in order to match coiling molds of different diameters, the workbench can be adjusted at will according to the diameter of the mold, which is convenient and quick to use.

6) Heat exchanger, in order to reduce the temperature of the control cabinet, a dedicated heat exchanger is added to cool down, which helps to slow down the aging of electrical components and keep the machine in the best operating state.

7) Carbide molds, the cutting and punching mold blades are made of carbide, and the effective shearing times can reach 300W times.

GREWIN INDUSTRIAL GROUP CO.,LTD.

Add: The fourth floor A-A3 zone aviation business area,Dongli Distr,Tianjin,China.



GREWIN INDUSTRIAL GROUP CO.,LTD.

TEL/WhatsApp: +86 18622096679

Mail: admin@coilwindingmachinechina.com

Web:www.coilwindingmachinechina.com



WhatsApp



WeChat

- 8) The machine is equipped with an automatic unloading device to facilitate operators to control and install materials.
- 9) The machine is equipped with a manipulator to collect materials to prevent the core from falling and causing injury.

(4) List of main accessories

NO.	Parts Name	QTY	Brand
1	Panasonic High-speed large-scale PLC control system	1	Japan
2	Delta 400W servo motor/actuator (for robot)	1	Taiwan
3	Delta 400W servo motor/actuator (For moving knife)	1	Taiwan
4	Delta 750W servo motor/actuator (Spindle winding)	1	Taiwan
5	Delta 750W servo motor/actuator (For material removal)	1	Taiwan
6	Delta 750W servo motor/actuator (For cutting)	1	Taiwan
7	Taiwan Shixie Precision Servo Reducer	2	Taiwan

GREWIN INDUSTRIAL GROUP CO.,LTD.

Add: The fourth floor A-A3 zone aviation business area,Dongli Distr,Tianjin,China.

**GREWIN INDUSTRIAL GROUP CO.,LTD.****TEL/WhatsApp: +86 18622096679****Mail: admin@coilwindingmachinechina.com****Web:www.coilwindingmachinechina.com**

WhatsApp



WeChat

8	Taiwan Weilun 10-inch touch screen	1	Taiwan
9	Hiwin Slider (20mm) Pipe Position and Manipulator	1pcs	Taiwan
10	Hiwin rail (20mm) pipe position and robot	0.5m	Taiwan
11	Hiwin Slider (15mm) Cutting edge	4pcs	Taiwan
12	Hiwin rail (15mm) Cutting edge	0.3m	Taiwan
13	Hiwin screw (40mm) for stripping	0.4m	Taiwan
14	Hiwin nut (40mm) for pipe	1pcs	Taiwan
15	Hiwin Screw (20mm) Robot	0.5m	Taiwan
16	Hiwin Nut(20mm) Robot	1pcs	Taiwan
17	Japan NSK precision screw bearing	3pairs	Japan
18	Carbide cutting die 1 set	1pcs	China
19	Korea Autonics Metal Sensor, Photoelectric Sensor	16	South Korea
20	Electrical components of electric control box(Fuji, idec, ABB, Siemens, Panasonic)		Japan/Europe
21	German Siemens button, emergency stop, warning lights, etc.		China

GREWIN INDUSTRIAL GROUP CO.,LTD.**Add: The fourth floor A-A3 zone aviation business area,Dongli Distr,Tianjin,China.**



GREWIN INDUSTRIAL GROUP CO.,LTD.

TEL/WhatsApp: +86 18622096679

Mail: admin@coilwindingmachinechina.com

Web: www.coilwindingmachinechina.com



WhatsApp



WeChat

GREWIN INDUSTRIAL GROUP CO.,LTD.

Add: The fourth floor A-A3 zone aviation business area,Dongli Distr,Tianjin,China.